

Compact.  
Sleek.  
Simple.

**WECO**

16A PV Input  
EPS Full Power



**ESY**

**SINGLE PHASE HYBRID INVERTER**

ESY Series is compact and lightweight, easy to use and install

# ESY SINGLE PHASE

## HYBRID INVERTER ( RAL 7016)



### Specifications

Specifications		ESY-3K	ESY-3.6K	ESY-4K	ESY-4.6K	ESY-5K	ESY-6K	ESY-8K
SOLAR	Nominal Input (PV) Power[kW]	3	3.6	4	4.6	5	6	8
	Max. Power[kW]	4.5	5.4	6	6.9	7.5	9	12
	Max. PV DC Voltage Voc [V]	500						
	MPPT Voltage Range [V]	80-450						
	Number of MPPT Trackers	2						
	Number of PV Strings input Each MPPT	1						1+2
	Max. Input Current of Single MPPT [A]	16						16/32
	max Short current (Isc) of Each MPPT [A]	18.5						18.5/37
AC OUTPUT	Rated Output Power [kW]	3	3.6	4	4.6	5	6	8
	Max. Output Current [A]	14.3	16	19.1	20	21.7	28.7	38.3
	Max. bypass Power [kW]	4.5	5.4	6	6.9	7.5	9	10
	Ac Output Voltage [Vac]	230						
	Frequency [Hz]	50/60						
	THDI	<3%						
BATTERY	Output Power Factor	1(0.8leading...0.8lagging)						
	Battery Voltage Range [V]	40-58						
	Max. Charging Voltage [V]	58.4						
	Max. Charge/Discharge Current [A]	60/60	72/72	80/80	92/92	100/100	120/120	160/160
	Battery Type	Li-Ion/Lead acid						
	Communication Interface	WeCo-CAN						
EPS OUTPUT	Rated power [kVA]	3	3.6	4	4.6	5	6	8
	Rated output voltage [V]	230						
	Rated output current [A]	13.1	15.65	17.39	20.0	21.74	26.09	34.78
	Rated frequency [Hz]	50/60						
	Automatic switching time [ms]	<10						
	THDI	< 2%						
GENERAL DATA	Overload capacity	110%, 60s / 120% 30s / 150%, 10s						
	Max. Efficiency	≥98.2%						
	Europe Efficiency	≥97%						
	Ingress Protection	IP65/NEMA 3R						
	Noise Emission [dB]	<35						
	Operating Temperature [°C]	-25 ~ 60						
	Cooling	Natural						
	Relative Humidity	0~95% (non-condensing)						
	Altitude	2,000m (>2,000 Derating)						
	Dimensions W *D *H [mm]	454x200x467						484x200x467
	Weight [kg]	19	19	19	19	19	19	22
	Isolation Transformer	No						
	Self-consumption [W]	<15						
	DISPLAY	Logic Multicolor LED bar	LED BAR					
	COM 1	RS485 WiFi						
	COM 2	USB Type-C						
SAFETY STANDARD	Certifications	EMC / CE / IEC 61000: 4 / 3IEC62109 / UK G / CEI021 Ask your distributor for specific Certifications available						



WeCo Srl a Socio Unico  
Viale J. F. Kennedy 113-121  
50038 Scarperia e San Piero  
Firenze, Italy

weco@wecobatteries.com  
www.wecobatteries.com



We recommend contacting WeCo for the most up-to-date datasheet, read warranty and manual before making any purchasing decisions. No part of this document can be copied or reproduced without WeCo written permission. All data is subject to change without prior notice.