

Meyer Burger White

Heterojunction Module – 375 Wp



Maximum performance:

Up to 20 percent more energy yield – even in low-light conditions, such as in the morning and evening hours or with cloudy skies




Maximum quality:

Production of solar cells and modules according to the highest standards and exclusively in Germany



Maximum durability:

Guaranteed yields for decades



Maximum stability:

Patented SmartWire technology makes the modules extremely rugged and efficient




Maximum elegance:

Understated and superb design – invented in Switzerland

Meyer Burger (Industries) GmbH


Carl-Schiffner-Str. 17
09599 Freiberg
Germany

www.meyerburger.com



MECHANICAL SPECIFICATION

Dimensions [mm]	1,767 x 1,041 x 35
Weight [kg]	19.7
Front Cover	Solar glass, 3.2 mm, with anti-reflective surface
Back Cover	High-barrier construction, white
Frame	Anodized aluminum [black]
Solar cell type	120 half-cut, mono n-Si, HJT
Junction boxes	3 diodes, IP68 rated, in accordance with IEC 62790
Cable	PV cable 4 mm ² , 1.2 m length, in accordance with EN 50618
Connectors	MC4, in accordance with IEC 62852, IP68 rated only when connected



ELECTRICAL SPECIFICATION¹


Power class in STC ² [W _p]		375		
Minimum Performance (Power Tolerance -0 W/+5 W)		[W _p]	STC	NMOT ³
Minimum	Power at MPP	P _{mpp} [W]	375	286
	Short Circuit Current	I _{sc} [A]	10.8	8.7
	Open Circuit Voltage	V _{oc} [V]	44.4	41.8
	Current at MPP	I _{mpp} [A]	10.2	8.2
	Voltage at MPP	V _{mpp} [V]	37.0	34.9
	Efficiency	η [%]	20.4	

Temperature Coefficients

Temperature Coefficient of I _{sc}	α	[%/°C]	+0.033
Temperature Coefficient of V _{oc}	β	[%/°C]	-0.234
Temperature Coefficient of P _{MPP}	γ	[%/°C]	-0.259
Nominal Module Operating Temperature	NMOT ³	[°C]	44±2

The temperature coefficients stated are linear values

Performance at different irradiance



PROPERTIES FOR SYSTEM DESIGN

Maximum System Voltage	[V]	1,000
Maximum Series Fuse Rating	[A]	15
Max. Test Load +/-, (incl. Safety Factor of 1.5)	[Pa]	6,000/4,000
Fire Class (classification pending)	C	
Operation Temperature	°C	-40 to +85

MEYER BURGER WARRANTY

Product Warranty [y]	25
Power Warranty [y]	25
Power after 1 year	≥98% of nominal power
Annual Degradation [%/y]	0.25
Power after 25 years	≥92% of nominal power

Warranty conditions apply

CERTIFICATES

Certifications

IEC 61215:2016, IEC 61730:2016

Certifications (to come)

UL61730-1, UL 61730-2, PID (IEC 62804), Salt Mist (IEC 61701), Ammonia Resistance (IEC 62716), Dynamical Mechanical Load (IEC, 62782:2016), Dust & Sand (IEC 60068)