




# TWMND

N-type Half-cell  
Bifacial Module (78)

## 78HD615-635W




[en.tongwei.com.cn](http://en.tongwei.com.cn)



Learn More

**DRAWINGS (Unit: mm)**



**MECHANICAL PARAMETERS**

Cells	TNC (N Type Monocrystalline Cell)
Cell Orientation	156[6X26]
Dimension	2465±2X1134±2X30mm
Weight	34.6kg
Front Glass	2.0mm high transmittance, AR semi-tempered glass
Rear Glass	2.0mm semi-tempered glass
Frame	Anodized aluminum alloy frame
Junction Box	IP68, 3 diodes
Output Cable	4.0mm <sup>2</sup>
Cable Length	+400mm, -200mm, length can be customized
Wind/Snow Load	2400Pa/5400Pa
Packaging	36pcs per pallet, 576pcs per 40'HC

**ELECTRICAL CHARACTERISTICS (STC)**

Module Type: TWMND-78HDXXX

Maximum Power: Pmax [W]	615	620	625	630	635
Open Circuit Voltage: Voc [V]	55.40	55.60	55.80	56.00	56.20
Short Circuit Current: Isc [A]	14.14	14.18	14.22	14.26	14.30
Voltage at Maximum Power: Vmp [V]	46.18	46.38	46.58	46.78	46.98
Current at Maximum Power: Imp [A]	13.32	13.37	13.42	13.47	13.52
Module Efficiency: η [%]	22.0	22.2	22.4	22.5	22.7

**ELECTRICAL CHARACTERISTICS (NMOT)**

Maximum Power: Pmax [W]	462.4	466.2	470.0	473.7	476.1
Open Circuit Voltage: Voc [V]	52.62	52.81	53.00	53.19	53.38
Short Circuit Current: Isc [A]	11.47	11.51	11.54	11.57	11.61
Voltage at Maximum Power: Vmp [V]	43.02	43.07	43.25	43.44	43.62
Current at Maximum Power: Imp [A]	10.72	10.79	10.83	10.87	10.91

\* STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass1.5, Measuring Tolerance: ±3%  
 \* NMOT: Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20°C, Air Mass1.5, Wind Speed 1m/s

**ELECTRICAL CHARACTERISTICS (Rear Power Gain)**

5%	Maximum Power: Pmax[W]	645.8	651.0	656.3	661.5	666.8
	Module Efficiency: η [%]	23.1	23.3	23.5	23.7	23.9
15%	Maximum Power: Pmax[W]	707.3	713.0	718.8	724.5	730.3
	Module Efficiency: η [%]	25.3	25.5	25.7	25.9	26.1
25%	Maximum Power: Pmax[W]	768.8	775.0	781.3	787.5	793.8
	Module Efficiency: η [%]	27.5	27.7	27.9	28.2	28.4


**TEMPERATURE PARAMETERS**

Temperature Coefficient (Pmax)	-0.30%/°C
Temperature Coefficient (Voc)	-0.25%/°C
Temperature Coefficient (Isc)	+0.046%/°C
NMOT	45±2°C


**MAXIMUM RATINGS**

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Output Tolerance	0~+5W
Maximum Bifaciality	80±5%

**WARRANTY**



**I-V CURVE**



**CERTIFICATIONS**

**Quality Management System and Product Certification**

- ISO 9001: 2015/Quality management system
- ISO 14001: 2015/Environmental management system
- ISO 45001: 2018/Occupation health safety management system
- ISO 50001: 2018/Energy management system
- IEC 62941: 2019/Quality system for PV module manufacturing
- IEC 61215/61730, IEC 62804(PID), IEC 61701(Salt), IEC 62716 (Ammonia), IEC 60068-2-68(Sand)

