




TSM-DE08M.08(II)



120 HALF-CUT
MONOCRYSTALLINE CELLS

360-385 W
POWER OUTPUT RANGE

21.0 %
MAXIMUM EFFICIENCY

0/+5 W
POSITIVE POWER TOLERANCE

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates

IEC61215/IEC61730/UL1703
IEC61701: Salt Mist Corrosion
IEC62716: Ammonia Corrosion
IEC60068: Blowing Sand
ISO9001; ISO14001; ISO45001; ISO14064



High power output

- Multi busbar technology combined with half-cut mono PERC cells for up to 385 W front power and 21.0 % module efficiency
- Reduced BOS costs with higher power bins and 1,500V system voltage



Great for residential rooftop application

- Maximize limited space with up to 210 W/m² power density
- Ultra-thin, virtually invisible busbars



Highly reliable due to stringent quality control


- Over 30 in-house tests (UV, TC, HF, and many more)
- In-house testing goes well beyond certification requirements
- PID resistant
- 2x 100% inline EL inspection




Certified to withstand challenging environmental conditions

- Salt Mist Corrosion
- Ammonia Corrosion
- Blowing Sand


PERFORMANCE WARRANTY




DIMENSIONS OF PV MODULE(mm)




Front View




Back View



I-V CURVES OF PV MODULE(370W)



P-V CURVES OF PV MODULE(370W)



ELECTRICAL DATA (STC)	TSM-360 DE08.M.08(II)	TSM-365 DE08.M.08(II)	TSM-370 DE08.M.08(II)	TSM-375 DE08.M.08(II)	TSM-380 DE08.M.08(II)	TSM-385 DE08.M.08(II)
Peak Power Watts-P _{MAX} (Wp)*	360	365	370	375	380	385
Power Tolerance-P _{MAX} (W)	0/+5	0/+5	0/+5	0/+5	0/+5	0/+5
Maximum Power Voltage-V _{MPP} (V)	33.6	33.9	34.2	34.4	34.7	34.9
Maximum Power Current-I _{MPP} (A)	10.70	10.76	10.82	10.89	10.96	11.04
Open Circuit Voltage-V _{OC} (V)	40.7	41.0	41.3	41.6	41.9	41.9
Short Circuit Current-I _{SC} (A)	11.24	11.30	11.37	11.45	11.52	11.58
Module Efficiency η_m (%)	19.6	19.9	20.2	20.5	20.7	21.0

STC: Irradiance 1000 W/m², Cell Temperature 25 °C, Air Mass AM1.5.
*Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)	TSM-360 DE08.M.08(II)	TSM-365 DE08.M.08(II)	TSM-370 DE08.M.08(II)	TSM-375 DE08.M.08(II)	TSM-380 DE08.M.08(II)	TSM-385 DE08.M.08(II)
Maximum Power-P _{MAX} (Wp)	271	275	279	283	287	290
Maximum Power Voltage-V _{MPP} (V)	31.5	31.8	32.0	32.2	32.5	32.7
Maximum Power Current-I _{MPP} (A)	8.60	8.65	8.71	8.77	8.83	8.89
Open Circuit Voltage-V _{OC} (V)	38.3	38.6	38.9	39.2	39.4	39.4
Short Circuit Current-I _{SC} (A)	9.06	9.10	9.16	9.23	9.28	9.33

NOCT: Irradiance at 800 W/m², Ambient Temperature 20 °C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	120 cells (6 × 20)
Module Dimensions	1763 × 1040 × 35 mm
Weight	20.0 kg
Glass	3.2 mm, High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA/POE
Backsheet	White
Frame	35 mm Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0 mm ² Portrait: N 280mm/P 280 mm Landscape: N 1200 mm /P 1200 mm
Connector	MC4 EVO2/TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2 K)
Temperature Coefficient of P _{MAX}	- 0.34%/K
Temperature Coefficient of V _{OC}	- 0.25%/K
Temperature Coefficient of I _{SC}	0.04%/K

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

MAXIMUM RATINGS

Operational Temperature	-40 to +85°C
Maximum System Voltage	1500V DC (IEC)
Max Series Fuse Rating	20A

WARRANTY

- 15 year Product Workmanship Warranty
- 25 year Power Warranty
- Max. 2% first year degradation
- Max. 0.55% Annual Power Degradation

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

- Modules per box: 31 pieces
- Modules per 40' container: 806 pieces