

# RESU 10M

9.8kWh Modular Type Battery Pack Specification

## RESU10M

### Electrical Characteristics

Total Energy Capacity	9.8 kWh
Usable Energy Capacity <sup>1)</sup>	9.3 kWh <sup>1)</sup>
Battery Capacity	63 Ah
Voltage Range	126.0 to 176.4 V <sub>DC</sub>
Nominal Voltage	155.4 V <sub>DC</sub>
Max. Charge/Discharge Current	39.6 A
Max. Charge/Discharge Power <sup>3)</sup>	5.0 kW
Battery Pack Round-Trip Efficiency	>95% (under specific condition)
Communication Interface	CAN 2.0B
DC Disconnect	Circuit Breaker, Contactor, Fuse

### Operating Conditions

Installation Location	Indoor / Outdoor (Wall-mounted / Floor Standing)
Operating Temperature	-10 to 50°C
Operating Temperature (Recommended)	15 to 30°C
Storage Temperature	-30 to 60°C : ~7 days -20 to 45°C : ~6 months
Humidity	5% to 95%
Altitude	Max. 2,000 m
Cooling Strategy	Natural Convection

### Certification

Safety	Cell	UL1642
	Battery Pack	IEC62619 / IEC60950(LVD) / CE
Emissions		IEC61000-6-1, IEC61000-6-3
Hazardous Materials Classification		Class 9
Transportation		UN38.3
Ingress Rating		IP55

※ Test Conditions - Temperature 25°C, at the beginning of life

※ Total Energy is measured under specific condition from LGC(0.3CCCV/0.3CC)

1) Value for Battery Cell Only (Depth of Discharge 95%). Actual usable energy at the AC output may vary by condition, such as the inverter efficiency and temperature.

## Mechanical Characteristics

		Module	Pack
Dimensions	Width	452 mm	452 mm
	Height	418 mm	511 mm
	Depth	120 mm	240 mm
Weight		36 kg	82 kg
Color		White (Module Color)	

\* BPU Unit : 10 kg



