Residential

FusionCharge AC





Single Phase

7.4 kW/32 A AP07N-EU

Three Phase

22 kW/32 A AP22N-EU



PV Power Preferred ¹

Power Your Car Completely with Solar

Make EV Even Greener

Automatic Phase Switch ²

More Usable Green Power

All on a Single App Automatic Switch between 1 Phase and 3 Phase Full Control Through One App





Dynamic Charging Power

Automatic Detection and Adjustment No Worry about Overload



3-Step Installation

Fast Installation in 16 Minutes Wiring-free Maintenance



Cable E-Lock for Anti-theft

Auto-Authentication

Bluetooth Auto-authentication Before Charging



		•
Technical Specification	AP07N-EU	AP022N-EU
	Inputs ar	nd Outputs
Charge power (configurable)	1.4 kW to 7.4 kW	1.4 kW ⁴ to 22 kW
Nominal voltage	230 V (1-phase) ± 20%	400 V (3-phase) ± 20%
Nominal current (configurable)	6–32 A (1-phase)	6–32 A (3-phase or 1-phase)
Nominal frequency	50 Hz/60 Hz ± 1 Hz	
Vehicle connection	Type 2 socket	
Cable width	Up to 10 mm ²	
Network types	TN, TT, IT	TN, TT
	User Interface &	Communications
Protocol	Modbus TCP	
Communication	Wi-Fi/Ethernet	
Charger status information	WRGB LED, App	
Authentication	RFID (ISO-14443-A), Bluetooth, App	
Remote control & monitoring	Арр	
Working mode	Normal Charge Scheduled Charge PV Power Preferred	
	Prot	ection
Cable protection	Cable E-Lock via App	
Residual current protection (RCD)	Type A + DC 6 mA integrated (IEC 62955 & IEC 61008-1)	
Fire Class	U	L94
Overcurrent protection	IEC 6	1851-1
Over-temperature protection)	'es
Surge protection	CA	AT II
	General Sp	pecifications
Operating temperature range	−35°C to +45°C	−35°C to +40°C
Application environment	Outdoor/Indoor	
Storage temperature	−40°C to +70°C	
Relative humidity	5% RH-95% RH	
Altitude	≤ 2000 m	
Dimensions (H x W x D)	335 mm x 180 mm x 145 mm	
Weight	3 kg 3.1 kg	
Installation mode	Wall-mounted	
IP rating	IP54	
Impact protection level	IK10	
Standby self-consumption	< 6 W	
	Standards Compliance (Mo	ore Available Upon Request)
itandard	EN 61851-1 2019, IEC 62955:2018, IEC 61008-1 2010, IEC/EN 62196-1	
	Ot	hers
Accessories	RFID Card * 2	
	TO TO COTO E	

^{*1} After 1 year free trail, it need to be activated by paid on APP.
*2 Available in Green Power Preferred Mode
*3 Available after Q4, 2022
*4 1.4 kW for 1-Phase Models and 4.2 kW for 3-Phase Models



Copyright © Huawei Technologies Co., Ltd.2020 All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice

, HUAWEI and are trademarks or registered remarks of Huawei Technologies Co., Ltd.

Other trademarks, product service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLGIES Dusseldorf GmbH

Südwestpark 37,90449 Nürnberg, Deutschland Hotline: +80 03 38 88 888

Email: eu_inverter_support@huawei.com

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base, Bantian Longgang Shenzhen 518129, P.R. China Tel.: 400-822-9999

Version No.: 04-(20201006) solar.huawei.com